




| | | | | | | | | | | | |
|-----|--------|--------------|--|---|--------------|----------|--|---|--|------------------|--|
| 1 | | 2 | | 3 | | 4 | | 5 | | Customer drawing | |
| REV | ECN NO | DESCRIPTION | | | DATE | APPROVED | | | | | |
| AA | - | NEW RELEASED | | | 2015. 09. 11 | CLARA | | | | | |



2 1
18 19






1 2
19 18



Electrical specifications:
 Use of voltage range: 30V
 Current range: 0.5A
 Temperature range: -20°C~+80°C

Material specifications
 Connector: HDMI Type-A Standard
 Connector: MICRO HDMI Type-D
 Overmolding: Black PVC
 Shell body: Aluminum alloy

Electrical testing of finished cable
 100% Open / Short / Miswiring testing
 Insulation resistance: DC150V 10MΩMin
 Conductor resistance: 3Ω Max

Manufacturer: Bomcan



| | | | | | | | |
|---|--------------------|--|--------|-------------------|-------|---|--|
|  <div style="display: inline-block; text-align: left;"> This drawing contains information that is proprietary to BOMCAN and should not be used without written permission. Powered by bomcan.com </div> | | | | | | | |
| DESCRIPTION | | MICRO HDMI PLUG/STANDARD HDMI SOCKET ADAPTER | | | | | |
| DWG NO | HDMI ADAPTER | BOMCAN PART No | | HDMI-ASDP-ADAPTER | | | |
| DRAWN BY | CLARA 2015. 09. 11 | CUSTOMER P/N | | - | | | |
| CHECKED BY | CALEB 2015. 09. 11 | SIZE: A4 | SHEET | UNIT | SCALE | Third angle projection | |
| APPROVED BY | BILL 2015. 09. 11 | REV: AA | 1 of 1 | MM | FREE |  | |